



3.5" Internal ALL in ONE USB3.0 Card Reader,

USB3.0 3 port HUB + 5V/12V Dual Power e-SATA/USB2.0 port

Model No.: INCRU3-HUB-PS

Features:

- Super Speed USB 3.0 interface fully backward compatibility with USB2.0/USB1.1 devices to upgrade your PC spec.
- USB3.0 Card Reader fully support SDXC, CF6 LBA48/UDMA7 and MS, XD, Micro SD, M2 Memory Cards.
- USB3.0 3port HUB extends more USB1.1/2.0/3.0 external applications.
- 5V/12V Dual Power e-SATA/ USB2.0 port supports 2.5"/3.5" Power e-SATA enclosure and adaptor and all USB2.0 applications.
- Provide one LED indicators for in-use status.
- Support Bus-powered, no external power required.
- Six Multi-luns supported and 5 kinds of memory cards copy/write synchronously.

• Card Reader/Writer

- Compatible With Universal Serial Bus Specification ver2.0 And Also Backward Compatible With USB1.1



Forcom Technology Co., Ltd.

Tel: +886-2-77296880 Fax: +8862-27585852

e-mail: info@forcomtech.com.tw

URL: <http://www.forcomtech.com.tw>

- USB 2.0 transfer rate up to 480Mbps ,backward USB 1.1 transfer up to 12Mbps
- Data copying between cards without storage intermediate, and it also allows you to upload photos/data from compatible media cards to a computer's hard driver
- Four card slots in-use one active LED
- It is compatible with Win ME, Windows 2000, Windows XP, Vista and WIN 7 operating system, it is also compatible with Mac OS 9.2 or higher operating system,

•Specification

Memory Slots XD / MS /SD/CF/M2/ T-flash slot	CompactFlash™, Secure Digital™ (SD), SDHC, miniSD, microSD (T-Flash), MultiMediaCard™ (MMC), RS-MMC, MMCmicro, MMCmobile, Memory Stick™ (MS), Memory Stick Duo™ (MS Duo), High Speed Memory Stick™ (HS MS), Memory Stick PRO™ (MS PRO), Memory Stick PRO™ Duo (MS PRO Duo), Memory Stick PRO-HG™ (MS PRO-HG), MS PRO Micro and xD-picture card on one chip. It also supports next generation high density memory cards (Capacity up to 2TB), such as SDXC and Memory Stick XC.
USB3.0 HUB	3 port USB3.0 compliant to USB1.1/2.0 and upto USB3.0 5Gbps data transfer. Each port chains up to 127 devices.
Indicator	One Active LED for Six card slot memory card / USB3.0 HUB and Power e-SATA/USB port
Bus Interface	USB3.0 for Card Reader and HUB; USB2.0/SATA for Power e-SATA/USB port
Power Supply	5V by USB Port, 12V by SATA 15PIN
Operating Temperature	0 ~ 70°C
Stock Temperature	20 ~ 60°C
Cable	Self-support USB 3.0 Cable, USB2.0 data cable, SATA 7 PIN data cable, SATA 15PIN power cable



Forcom Technology Co., Ltd.

Tel: +886-2-77296880 Fax: +8862-27585852

e-mail: info@forcomtech.com.tw

URL: <http://www.forcomtech.com.tw>

Dimensions	109(L)*102.1(W)*25.4(H)mm
Weight	300g