



## PCIe USB3.0 2 port Express card with Low profile

**MODEL NO.: PEU3P2L**

### Features

- Supports PCI Express Base Specification Revision 2.0.
- Single-lane ( x1) PCI Express throughput rates up to 5 Gbps.
- Compliant with Universal Serial Bus 3.0 specification Revision 1.0.
- Compliant with xHCI(eXtensibleHost Controller Interface) specifications Revision 0.95.
- Supports simultaneous operation of multiple USB 3.0, USB 2.0 and USB 1.1 devices
- Supports USB data transfer rate of 1.5/12/480/5000 Mbps.
- Expands two external USB3.0 Super-Speed ports on the system.
- Each USB port supplies maximum +5V / 900mA power output to USB device.
- Built-in 4-pin power connector for receiving extra power supply from system.
- Hot-swapping feature allows you to connect/disconnect devices without powering down the system.
- Driver supports for Microsoft Windows 2000, XP, Vista, and 7 operation system.
- Certified by CE, FCC, RoHS, and Microsoft WQHL approval.

### **Specification Specification**

Interface: PCI-E X1

Mode: USB3.0

Controller: NEC  $\mu$ PD720200



**Forcom Technology Co., Ltd.**

Tel: +886-2-77296880 Fax: +886-2-27055495

e-mail: [info@forcomtech.com.tw](mailto:info@forcomtech.com.tw)

URL: <http://www.forcomtech.com.tw>

Port: 2 external USB3.0 ports

Speed: Data Transfer rate of 1.5/12/480/5000 Mbps.

Low Speed (1.5Mbps), Full Speed(12Mbps), High Speed(480Mbps), Super Speed(5Gpbs)

Power Output: +5V / 900mA

O.S. support: Windows2000/XP/2003/Vista/7, (32/64-bit)

Environment : Operation temp. 0 °C ~ 57 °C

Operation humidity: 5 ~ 95% RH

Storage temp.-20 °C ~ 85 °C