



## PCI 2 port Serial (RS232) Low profile

Model No.: SER5232LR2

### Feature:

- 2 independent RS-232 serial ports with communication speeds up to 230 ( 921 ) Kbps
- PCI compatible with 64/32-bit PCI-X/PCI Bus and 3.3/5V connector key
- High speed 16C950 compatible UART controller on-board
- Super IEEE 1284 Parallel ports standard  
ECP ( Enhance Capacity Port ) / EPP ( Enhance Parallel Port ) / SPP ( Standard Parallel Port )
- On-chip hardware auto flow control to guarantee no data loss
- Built-in 32 byte hardware FIFO & 128K byte DMA software FIFO
- Certified by Microsoft WHQL,CE,FCC approval
- Support DOS, Linux, Microsoft Windows 98/ME/NT/2000/XP/2003 and Vista
- Ready of the Intel and AMD 32/64-bit CPU System

### Spec.:

#### Serial communication

<b>Interface</b>	RS-232+Paralle
<b>Controller</b>	OXFORD OX16PCI952
<b>Bus</b>	32-bit PCI
<b>No. of port</b>	3 ports
<b>Port Type</b>	DB44 Female
<b>IRQ &amp; IO</b>	Assigned by System
<b>FIFO</b>	32 byte Hardware & 128K byte DMA FIFO
<b>Baud rate</b>	96bps ~ 230 ( 921 ) Kbps
<b>Flow Control</b>	None , Xon/Xoff , RTS/CTS
<b>Baud Rate</b>	up to 1.5Mbps



## Forcom Technology Co., Ltd.

Tel: +886-2-77296880 Fax: +886-2-270535495

e-mail: [finfo@forcomtech.com.tw](mailto:finfo@forcomtech.com.tw)

URL: <http://www.forcomtech.com.tw>

**Mode** SPP/EPP/ECP

### Driver Support

**Microsoft** Windows 98/ME/NT/2000/XP/2003/Vista ( 32/64-bit )

**Linux Kernel** 2.4.x/2.6.x

**DOS** DOS

### Regulatory Approvals

**Hardware** CE , FCC

**Software** WHQL

### Operation Environment

**Operation Temperature** 0 to 60°C

**Operation Humidity** 5 to 95% RH